



3518 / 3518 P

3518 - Compactor with vibratory smooth roller drum

3518 P - Compactor with vibratory padfoot drum



- ▶ Ergonomic driver seat for perfect all-round visibility
- ▶ Clear information display
- ▶ Excellent hill climbing ability via self-locking differential
- ▶ 3-point swivel joint for optimum driving comfort
- ▶ Hydrostatic steering
- ▶ Optimum ease of maintenance, long service intervals



3518 / 3518 P

3518 - Compactor with vibratory smooth roller drum
3518 P - Compactor with vibratory padfoot drum



	3518	3518 P
Weights		
Operating weight with ROPS	kg 17605	17805
Operating weight with cab	kg 17825	18025
Operating weight, max.	kg 21420	19760
Axle load, front/rear	kg 10785/7040	10985/7040
Load per tyre, rear	kg 3520	3520
Static linear load, front	kg/cm 48,6	
French classific., data/class	68,73/VM4	68,77/VPM4
Machine dimensions		
Max. working width	mm 2220	2220
Lateral overhang, left/right	mm 85/85	85/85
Ground clearance, left/right	mm 510/510	510/510
Ground clearance, centre	mm 425	425
Turning radius, inside	mm 4435	4180
Drum type, front	smooth/nondivided	Padfoot
Drum thickness, front	mm 45	35
Number of padfeet		150
Height of the padfeet	mm 100	100
Front area of padfeet	cm ²	152
Size of tyres, rear	AW 23.1-26 12 PR	TR 23.1-26 12 PR
Diesel engine		
Manufacturer	DEUTZ	DEUTZ
Type	TCD 2012 L06 2V	TCD 2012 L06 2V
Number of cylinders	6	6
Power rat. ISO 14396, kW/PS/rpm	155,0/210,8/2300	155,0/210,8/2300
Power rating SAE J1349, kW/HP/rpm	155,0/207,7/2300	155,0/207,7/2300
Emissions standard EU/USA	III A / Tier 3	III A / Tier 3
Fuel tank, capacity	L 290	290
Drive		
Hydrostatic drive, front/rear		Hydraulic motor/axle
Speed, working gear	km/h 0-4,2/0-5,6/0-6,7	Hydraulic motor/axle 0-3,8/0-5,3/0-5,9
Speed, transportation gear	km/h 0-11,4	0-11,1
Climbing ability, vibration on/off	% 48/53	55/60
Vibration		
Vibration frequency, front, I/II	Hz 27/30	27/30
Amplitude, front, I/II	mm 2,00/1,19	1,93/1,15
Centrifugal force, front, I/II	kN 331/243	331/243
Steering		
Steering, type	Articulated steering	Articulated steering
Steering, actuation	hydrostatic, steering wheel	hydrostatic, steering wheel
Steering angle +/-	32	32
Oscillation angle +/-	10	10

Equipment
Spring-mounted driver seat, Double-sided access, Seat console, can be moved and swivelled laterally, Continuously variable hydrostatic all-wheel drive, Excellent engine power with traction control, Swivelling steering and instrument console, Modern information and indicator display, Tiltable GRP bonnet

Optional equipment
Spotlights, Exterior and interior mirrors, Radio, Heating with dust-free ventilation, Air conditioning, ROPS/FOPS, Sound insulation, Sunroof, HCQ compression meter, HCQ GPS compression documentation, Tachograph

Total length	L	6440	6210
Width	B	2390	2390
Total height	H	2980	3050
Wheel base	A	3252	3165
Roller drum width	X	2220	2220
Drum diameter	D	1600	1784
Width over tyres	Y	2160	2160
Diameter of tyres	R	1565	1565
Height loading, min.	HI	2325	2350

